

R.S.BATEMAN LTD - ACRYLIC ADHESIVE MATERIAL DATA SHEET

1. Identification

Material:- Acrylic Flooring Adhesive

Ref:- R40

Date of issue- 01/03/2010

Company ~ R.S.Bateman Ltd
Concord House
34 Nesfield Street
Bradford
BD1 3ET

(Tel) 01274 394904 (Fax) 01274 306882 (E-mail) sales@carpet-accessories.co.uk

2. Composition

Adhesive preparation containing a blend of aqueous acrylic emulsion, resins, mineral filler and surfactants.

3. Hazards Identification

On available data this product is not a dangerous preparation in the sense of the EC-Directive on Classification and Declaration.

4. First Aid Measures

Inhalation – Proceed to fresh air.

Skin Contact - Wash affected area of skin with plenty of soap and water.

Eye Contact – Irrigate immediately with plenty of water or proprietary eye wash and seek medical help.

Ingestion – Do not induce vomiting. Clean out mouth with water and discard, then give water to drink. Seek medical help.

5. Fire Fighting Measures.

Product is water based and non-flammable.

6. Accidental Release Measures.

Prevent spillage from entering drains or other water courses. Scoop up, then soak up the remainder with earth or sand and allow to dry

7. Handling and Storage.

7.1 Handling – Wash hands before breaks and end of work. Avoid smoking, eating or drinking during handling and avoid contact with skin or eyes.

7.2 Storage – Keep container properly sealed and at a temperature between 5°C and 30°C. Protect containers from mechanical damage.

8. Exposure Controls and Personal Protection.

8.1 – Ensure provision of a well-ventilated area of work.

8.2 – Wear suitable protective clothing.

R.S.BATEMAN LTD - ACRYLIC ADHESIVE MATERIAL DATA SHEET - CONTINUED

9. Physical and Chemical Appearance.

Appearance	Milky white fluid
Odour	Slightly Ammonia
pH	8.5 – 9.5
Flash Point	Not Applicable
Ignition Temperature	Not Applicable
Explosion Temperature	Not Applicable
Boiling Point Range	100°C (as water)
Freezing Point Range	0°C (as water)
Specific Gravity	Approx. 1.2
Viscosity	Approx. 45,000 cpts at 20°C

10. Stability and reactivity.

No thermal decomposition, hazardous decomposition products or hazardous reactions when stored and used as designated. Avoid contact with strong acids, metals and materials which react with water.

11. Toxicological Information.

According to our present knowledge and practical experience this product is not expected to be harmful to health when properly used as designated.

Ingestion – Not evaluated but would expect gastric discomfort.

Eyes – Possible irritant.

Skin – Frequent or prolonged contact may cause irritation.

12. Ecological Information.

Not established. Product should not be discharged to surface water.

Do not allow to enter sewers or watercourses

13. Disposal Considerations.

Dispose of material in accordance with national and local regulations for waste materials.

14. Transport Information.

Not classified as dangerous for transportation.

15. Regulatory Information.

Not classified as dangerous for supply. No labelling as required.

16. Other Information

Application – Flooring adhesive.

LEGAL DISCLAIMER – The above information is believed to be correct but does not purport to be all-inclusive and shall only be used as a guide. R. S. Bateman Ltd, shall not be held liable for any damages resulting from handling or contact.